



**DDS-225 – Dual Drum Sander**

- Plenty of power and robust for production sanding
- Micro adjustable rear sanding drum to allow different chip removal
- Quick change of abrasive strips
- 75mm and 100 mm wide abrasive strips can be used
- Hard-rubber coated sanding drums guarantee best working results
- The conveyor bed is guided on 4 solid jackscrews
- The 2 speed gearbox can match feed to different types of wood
- Two 100 mm dust ports promote a clean work environment

2 sanding drums for roughing and finishing in one operation

**Standard equipment**

- 2x 100-mm dust port
- Closed cabinet stand
- One abrasive strip 80 grit
- One abrasive strip 100 grit

**Accessories**

Stock number	Description
708119	Mobile base up to 500 kg
60-0505	Abrasive stripe cleaning stick
Abrasive strips see page 38.	

<b>Stock number 400 V</b>	<b>1791290 T</b>
Model:	DDS-225
Sanding capacity	
Max. width:	635 mm
Min. length:	230 mm
Max. thickness:	133 mm
Min. thickness:	0.8 mm
Drums:	2x Ø 152x635 mm
Speed:	1400 rpm
Abrasive strips width:	75 mm or 100 mm
Feed speed:	2 or 3m/min
Feed motor power:	0.25 HP
Dust ports:	2x Ø 100 mm
Motor power output:	5 HP/S <sub>1</sub> 100%
Motor power input:	7.5 HP/S <sub>6</sub> 40%
Weight:	332 kg
Dimensions L x W x H:	1090x1120x1090 mm